

SAFETY DATA SHEET

1. Identification

Product number	1000001358
Product identifier	TERAND CHAIN & CABLE LUBRICANT
Revision date	04-29-2016
Company information	CPC 1005 S. Westgate Drive Addison, IL 60101 United States
Company phone	General Assistance 800-327-1835
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	05
Supersedes date	09-07-2015
Recommended use	Lubricant
Recommended restrictions	None known.
2. Hazard(s) identification	

Physical hazards	Flammable aerosols	Category 1
Health hazards	Sensitization, skin	Category 1
	Specific target organ toxicity, repeated exposure	Category 1
OSHA defined hazards	Not classified.	

OSHA defined hazards

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.
Response	If on skin: Wash with plenty of water. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates, (Petroleum), Hydrotreated Heavy Paraffinic		64742-54-7	60 - 80
Propane		74-98-6	10 - 20

Chemical name	Common name and synonyms	CAS number	%
Mineral Spirits		8052-41-3	2.5 - 10
Cocoyl Diethanolamide		68603-42-9	1 - 2.5
Solvent Naphtha (Petroleum), Medium Aliphatic		64742-88-7	1 - 2.5
Diethanolamine		111-42-2	0.1 - 1
Sulfonic Acids, Petroleum, Calcium Salts		61789-86-4	0.1 - 1
Other components below reportable	levels		2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose balder or mapiter particles if passible. If pet withdraw and let fire burn out

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 3 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	ts for Air Contaminants (29 CFR 1910.1 Type	Value	
Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m3	
,		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Lin	nit Values		
Components	Туре	Value	Form
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm	·
US. NIOSH: Pocket Guide	e to Chemical Hazards		
Components	Туре	Value	
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3	
,		3 ppm	
Mineral Spirits (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
logical limit values	No biological exposure limits noted for	or the ingredient(s).	
osure guidelines			
US - California OELs: Ski	n designation		
Diethanolamine (CAS US ACGIH Threshold Lim	111-42-2) Can I it Values: Skin designation	be absorbed through the skin.	
Diethanolamine (CAS	111-42-2) Can I	be absorbed through the skin.	
propriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establ	pplicable, use process enclosu tain airborne levels below reco	res, local exhaust ventilatic mmended exposure limits.
ividual protection measure Eye/face protection	es, such as personal protective equipm If contact is likely, safety glasses with		d.
Skin protection			
Hand protection	Wear appropriate chemical resistant supplier.	gloves. Suitable gloves can be	recommended by the glove
	Wear appropriate chemical resistant		

Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

••••••••••••••••••••••••••••••••••••••	
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	302 °F (150 °C) estimated
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	80 - 90 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.802 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Information on likely routes o Inhalation	May cause damage to organs through prolong	ged or repeated exposure by inhalation.	
Skin contact	May cause an allergic skin reaction.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	toms related to the May cause an allergic skin reaction. Dermatitis. Rash. cal, chemical and		
Information on toxicological e	effects		
Acute toxicity	May cause an allergic skin reaction.		
Components	Species	Test Results	
Diethanolamine (CAS 111-42-2)		
<u>Acute</u>			
Oral			
LD50	Rat	1100 mg/kg	
Distillates, (Petroleum), Hydrotro <u>Acute</u>	eated Heavy Paraffinic (CAS 64742-54-7)		
Dermal			
LD50	Rabbit	> 2000 mg/kg	
		> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Rat	2.18 mg/l, 4 Hours	
Oral	- /		
LD50	Rat	> 2000 mg/kg	
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes	
LUUU	INDUSE	-	
	Pot	52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
Acute	/ledium Aliphatic (CAS 64742-88-7)		
Dermal	Dakkit		
LD50	Rabbit	> 2000 mg/kg	
		> 2000 mg/kg, 24 Hours	
Inhalation LC50	Cot		
LUOU	Cat	> 6.4 mg/l, 6 Hours	
	Rat	> 7.5 mg/l, 6 Hours	
		> 4.3 mg/l, 4 Hours	
		> 0.1 mg/l, 8 Hours	
Oral			
LD50	Rat	> 5000 mg/kg	
ulfonic Acids, Petroleum, Calc <u>Acute</u>	ium Salts (CAS 61789-86-4)		
Dermal			
LD50	Rabbit	> 4000 mg/kg, 24 Hours	
	Rat	> 2000 mg/kg, 24 Hours	

Components	Species	;		Test Results
Inhalation				
LC50	Rat	Rat > 1.9 mg/l, 4 Hours		> 1.9 mg/l, 4 Hours
Oral				
LD50	Rat		:	> 5000 mg/kg
* Estimates for product may	be based on a	additional compone	nt data not shown.	
Skin corrosion/irritation	Prolonged	skin contact may c	ause temporary irritation.	
Serious eye damage/eye irritation	Direct con	tact with eyes may	cause temporary irritation	
Respiratory or skin sensitization	on			
Respiratory sensitization	Not a resp	iratory sensitizer.		
Skin sensitization	May cause	e an allergic skin rea	action.	
Germ cell mutagenicity		vailable to indicate or genotoxic.	product or any component	ts present at greater than 0.1% are
Carcinogenicity	Risk of ca	ncer cannot be excl	uded with prolonged expo	osure.
IARC Monographs. Overal	I Evaluation	of Carcinogenicity		
Cocoyl Diethanolamide Diethanolamine (CAS 1 OSHA Specifically Regula	11-42-2)		2B Possibly carcinogen 2B Possibly carcinogen 001-1050)	
Not regulated. US. National Toxicology P Not listed.		-		
Reproductive toxicity	This produ	uct is not expected t	o cause reproductive or d	evelopmental effects.
Specific target organ toxicity - single exposure	-	Not classified.		
Specific target organ toxicity - repeated exposure	Causes da	Causes damage to organs through prolonged or repeated exposure.		
Aspiration hazard	Not likely,	Not likely, due to the form of the product.		
Chronic effects		Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.		
12. Ecological information	n			
Ecotoxicity	The produ			ous. However, this does not exclude the ul or damaging effect on the environment.
Components		Species		Test Results
Diethanolamine (CAS 111-4	2-2)			
Aquatic				
Algae	IC50	Algae		7.8 mg/L, 72 Hours
Crustacea	EC50	Daphnia		55 mg/L, 48 Hours
Fish	LC50	Fathead minn	ow (Pimephales promelas	i) 100 mg/l, 96 hours
Solvent Naphtha (Petroleum Aquatic	ı), Medium Ali	phatic (CAS 64742-	-88-7)	
Crustacea	EC50	Daphnia		100.0001 mg/L, 48 Hours
* Estimates for product may	be based on a	additional compone	nt data not shown.	
Persistence and degradability		-	egradability of this product	t.
Bioaccumulative potential				
Partition coefficient n-octa	inol / water (l	og Kow)	-1.43	
Mineral Spirits			- 1.45 3 16 - 7 15	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

/1	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None


This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U

Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code DOT

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. LTD QTY Not applicable.



15. Regulatory informatio	n		
US federal regulations	This product is a "Hazardou Standard, 29 CFR 1910.12		ned by the OSHA Hazard Communication
TSCA Section 12(b) Export	Notification (40 CFR 707, Su	ıbpt. D)	
Not regulated.			
CERCLA Hazardous Substa	ance List (40 CFR 302.4)		
Diethanolamine (CAS 11		Listed.	
SARA 304 Emergency relea	se notification		
Not regulated.			
	ed Substances (29 CFR 1910	.1001-1050)	
Not regulated.			
Superfund Amendments and Re	•	SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No		
SARA 302 Extremely hazar	dous substance		
Not listed.			
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting)			
Chemical name		CAS number	% by wt.
Diethanolamine		111-42-2	0.1 - 1
Other federal regulations			
Diethanolamine (CAS 11	,	. ,	
Clean Air Act (CAA) Section Propane (CAS 74-98-6)	n 112(r) Accidental Release	Prevention (40 CFR	68.130)

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Cocoyl Diethanolamide (CAS 68603-42-9) Diethanolamine (CAS 111-42-2) Distillates, (Petroleum), Hydrotreated Heavy Paraffinic (CAS 64742-54-7) Mineral Spirits (CAS 8052-41-3)

US. Massachusetts RTK - Substance List

Diethanolamine (CAS 111-42-2) Mineral Spirits (CAS 8052-41-3) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Diethanolamine (CAS 111-42-2) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Diethanolamine (CAS 111-42-2) Mineral Spirits (CAS 8052-41-3) Propane (CAS 74-98-6)

US. Rhode Island RTK

Diethanolamine (CAS 111-42-2) Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2)	Listed: June 22, 2012
Ethyl Benzene (CAS 100-41-4)	Listed: June 11, 2004
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-27-2015
Revision date	04-29-2016
Version #	05

Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Product and Company Identification: Alternate Trade Names Composition/information on ingredients: Component information Fire-fighting measures: General fire hazards Accidental release measures: Personal precautions, protective equipment and emergency procedures Accidental release measures: Methods and materials for containment and cleaning up Handling and storage: Precautions for safe handling Exposure controls/personal protection: PPE Symbols Other information, including date of preparation or last revision: Disclaimer GHS: Classification