

PRODUCT TECHNICAL DATA SHEET

SW066 Spray Adhesive

SPECS:

DESCRIPTION:

A high-performance product perfect for use in the art studio, graphic arts or screenprinting shop, or the sign shop. No. 66 is a non-wrinkling, repositionable, water-resistant, quick or long tack adhesive that provides either a temporary or permanent bond.

USES:

This spray can be used to bond many materials including: metal, cardboard, foam rubber, plastic films, glass, wood, paper and cloth. Ideal for quick layouts, paste-ups, labeling and display assembly.

Can Size: 16 oz.

	Net Weight:	11 oz.
	Shipping Weight:	11 lbs.
	Packaged:	12 cans per case
	UPC Number:	0 41911 00066 6
PHYSICAL	Color:	Tan, semi-translucent
CHARACTERISTICS:	Fragrance:	Solvent
	Shelf Life:	1 Year +
REGULATORY:	Ozone Depleting Compounds:	None
	Recyclable Packaging:	Yes
	VOC Compliant CARB/OTC:	No
	CPSC Flame Extension:	Required to be labeled as extremely flammable per 16 CFR 1500
	24 HOUR MEDICAL EMERGENCY:	1-866-836-8855
	· · · · · · · · · · · · · · · · · · ·	



PRODUCT FEATURES: •

- Permanent or temporary bond
- Non-wrinkling
- Quick tack
- Water resistant

AFTER USE: to clear valve of adhesive - hold can bottom up and spray a small amount. Spray tips may be cleaned with turpentine.