

RTV SILICONE GASKET MAKER

115 - Red (High Temp)



SILICONE GASKET MAKER RED (HIGH TEMPERATURE) 115

Seals, Bonds, Insulates
Low Volatile • Flexible • Easy to Use
Economical • Eliminates Waste
Waterproof • Weatherproof
Eliminates: Squeeze Tubes and Cartridg

Eliminates: Squeeze Tubes and Cartridge Guns 100% Low Volatile R.T.V. Silicone

Meets G.M. and O.E.M. specifications Safe to use on oxygen sensor equipped vehicles

Pressurized dispenser makes any size or shape gasket instantly

Remains permanently flexible at temperatures from -60°F to +600°F Eliminates need to stock conventional gaskets and seals

Reduces down time - gets equipment back in operation fast

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER. SEE OTHER CAUTIONS ON BACK PANEL KEEP OUT OF REACH OF CHILDREN. NET WT. 8 OZ. (227 Grams)

This R.T.V. Sealant Adhesive can be used on metal, glass, porcelain, ceramics, wood, rubber, and most paint and plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink. Withstands intermittent temperatures up to 650°F and pressures up to 330 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging.



FEATURES

- Seals, Bonds, Insulates Low Volatile Flexible
- Easy to Use Economical Eliminates Waste
- Waterproof Weatherproof
- Eliminates: Squeeze Tubes & Cartridge Guns
- 100% Low Volatile R.T.V. Silicone
- Meets G.M. and O.E.M. specifications
- · Safe to use on oxygen sensor equipped vehicles



FOR USE ON

Pumps, High Pressure Pipe Joints, Oil and Transmission Pans, Oil and Water Pumps, Valve and Timing Chain Covers, Electric Motors and Electrical Control Boxes, Gear Boxes, Compressors, Machine Covers, Rigid Flange Assemblies, Equipment Housings

Characteristics:	
Temperature Range	Cures at room temperature, range from -60°F to +650°F
Waterproof	Yes
Appearance	Red Paste
Shipping Weight	12 pounds





